

T 225 D



Vehicle type	T 225 D
Operating areas	Distribution-/Logistic Centers and Industry
System load	up to 60 ton (132,300 lbs.) (GCW)
Engine	Diesel engine
Tractor weight	approx. 8.000 kg (17,650 lbs.)
Type of engine	Cummins or VOLVO from each 129kW up to 172kW (175 HP/233 HP) (depending on exhaust emission stage IIIA, IV or V)
Transmission	ZF 5WG191 or Allison 3000P
5th wheel plate	Holland Eurohitch 3510-TR for 2" kingpin
Lifting capacity	up to 25.000 kg (55,115 lbs.)
Wheel base	3.500 mm (137,8")
Speed	up to 40 km/h (25 mph)
Axles	Front axle type VOLVO Rear axle type Kessler
Cabin	ROPS and FOPS certified With one side door, access via the platform Windshield and rear window made of laminated glass

Please see our technical data sheet for more information

MAFI T 225 D

Your Terminal Tractor For Distribution Center Operations

The T 225 D distribution tractor is used especially for moving semi-trailers in distribution and logistics centers. The longer wheelbase allows for significantly more free space between the semi-trailer and the driver's cab.

As a result, the brake and power supply for the semi-trailer can be connected faster. The driver works safely, comfortably and effectively, without ever leaving the vehicle platform. Low coupling heights can be guaranteed by the use of the appropriate tires.

Using the tractor to lift the coupled semitrailer hydraulically eliminates the time-consuming raising and lowering of the trailer's landing legs. As a result, the T 225 D can move 3 – 4x more semitrailers than a conventional road truck.



Featured vehicles in photos may include additional equipment.